

Twin Halogen Floodlights



The Bardic Twin Halogen Floodlight emergency luminaire is designed to provide emergency lighting to large high ceiling areas, such as factories and warehouses.

Features

- Designed and tested to comply with AS/NZS 2293
- Automatic battery low voltage cut-out to prevent overdischarge of the battery
- Available with Sealed Lead Acid or Nicad Batteries
- 8 minutes "off" delay – the luminaire remains illuminated for 8 minutes following restoration of the A.C. mains supply to allow High Bay lights to strike
- High temperature components for extended life
- Red L.E.D. indicates a healthy A.C. mains supply and functioning charger
- Test switch to test the emergency operation while A.C. mains is healthy

MH BARDIC
POWER SYSTEMS emergency lighting

2 x 10 WATT TWIN SPOTS SPECIFICATION

AUSTRALIA
Head Office:
 9 Mosrael Place
 Rowville Victoria 3178
 Telephone: (61 3) 9763 0555
 Facsimile: 1300 733 005

New South Wales:
 Unit 21/14 Stanton Road
 Seven Hills NSW 2147
 Telephone: (61 2) 9674 3199
 Facsimile: 1300 733 005

Queensland:
 12 The Corso
 Seven Hills QLD 4170
 Telephone: (61 7) 3902 0902
 Facsimile: 1300 733 005

South Australia:
 89A Grange Road
 Allenby Gardens SA 5009
 Telephone: (61 8) 8340 4081
 Facsimile: 1300 733 005

Western Australia:
 B-Type Agencies Pty Ltd
 Unit 2/15 Narloo Street
 Malaga WA 6090 Perth
 Telephone: (61 8) 9209 2220
 Facsimile: (61 8) 9209 2229
 Email: Infor@btype.com.au

Tasmania
 Cables Plus (Tas) Pty Ltd
 8 Devon Street
 South Bernie TAS 7320
 Telephone: (61 3) 6431 8660
 Facsimile: (61 3) 6431 4430

NEW ZEALAND
Auckland
 Unit B 237 Bush Road
 Albany, Auckland
 Telephone: (649) 415 6615
 Facsimile: (649) 415 8160

Wellington
 Unit 7 30-32 Downer Street
 Lower Hutt, Wellington
 Telephone: (644) 586 6188
 Facsimile: (644) 586 6088

Christchurch
 8 Kirkdale Place
 Avonhead, Christchurch
 Telephone: (643) 358 8444
 Facsimile: (643) 358 8446

	CIL502S	CIL502SWP	CIL502NS
Function	Non Maintained	Non Maintained	Non Maintained
Battery	Lead Acid	Lead Acid	Nicad
Emergency duration after a 16 Hour recharge on commissioning	2 Hour Minimum	2 Hour Minimum	2 Hour Minimum
Power Consumption (Maximum)	10VA	10VA	10VA
Input Voltage	240VAC	240VAC	240VAC
Frequency	50 Hz	50 Hz	50Hz
Environment	Indoor	Outdoor	Indoor
Standards	AS/NZS 2293	AS/NZS 2293	AS/NZS 2293
Body Construction	Folded Sheet Steel	Fibre Glass Reinforced Polyester (Polycarbonate Diffuser)	Folded Sheet Steel
IP Classification	IP21	IP66	IP21
Charger	Constant Voltage	Constant Voltage	Dual Rate
Sentinel Compatible	Yes	Yes	Yes
Weight	5.5kg	5.5kg	5.5kg
Length	365mm	380mm	365mm
Width	85mm	135mm	85mm
Height	223mm	190mm	223mm
Overall Height	375mm	345mm	375mm

