

SBP Series (AC-Coupled)

Single Phase AC Retrofit Storage Solution (LV Battery)



Technical Data		GW3600S-BP	GW5000S-BP
Battery Input Data	Battery Type	Li-Ion	
	Nominal Battery Voltage (V)	48	
	Max. Charging Voltage (V)	≤60 (Configurable)	
	Max. Charging Current (A)* ¹	75	100
	Max. Discharging Current (A)* ¹	75	100
	Battery Capacity (Ah)* ²	50~2000	
	Charging Strategy for Li-Ion Battery	Self-adaption to BMS	
AC Output Data (On-grid)	Nominal Power Output to Utility Grid (W)	3680	5000
	Max. Apparent Power Output to Utility Grid (VA)	3680	5000
	Max. Apparent Power from Utility Grid (VA)	7360	9200
	Nominal Output Voltage (V)	230	
	Nominal Output Frequency (Hz)	50/60	
	Max. AC Current Output to Utility Grid (A)	16	21.7
	Max. AC Current from Utility Grid (A)	32	40
	Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)	
	Output THDi (@Nominal Output)	<3%	
AC Output Data (Back-up)	Max. Output Apparent Power (VA)* ³	3680	5000
	Peak Output Apparent Power (VA)* ³	4416, 10sec	5500, 10sec
	Automatic Switch Time (ms)	<10	
	Nominal Output Voltage (V)	230 (±2%)	
	Nominal Output Frequency (Hz)	50/60 (±0.2%)	
	Max. Output Current (A)	16	22.8
	Output THDv (@Linear Load)	<3%	
Efficiency	Max. Efficiency	95.5%	
Protection	Anti-Islanding Protection	Integrated	
	Output Over Current Protection	Integrated	
	Output Short Protection	Integrated	
	Output Over Voltage Protection	Integrated	
General Data	Operating Temperature Range (°C)	-25~60	
	Relative Humidity	0~95%	
	Operating Altitude (m)	4000	
	Cooling	Nature Convection	
	Noise (dB)	<25	
	User Interface	LED & APP	
	Communication with BMS* ⁴	RS485; CAN	
	Communication with Meter	RS485	
	Communication with Portal	Wi-Fi* ⁵	
	Weight (kg)	18.5	
	Size (Width*Height*Depth mm)	347*432*190	
	Mounting	Wall Bracket	
	Protection Degree	IP65	
	Standby Self-Consumption (W)	<15	
	Topology	High Frequency Isolation	

*:The actual charge and discharge current also depends on the battery.

*: Battery capacity could be not less than 100Ah where the back-up function is to be applied.

*: Can be reached only if battery capacity is enough, otherwise will shut down.

*: The standard configuration is CAN.

*: Only compatible with 2.4Ghz network.

*: Please visit GoodWe website for the latest certificates.

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

T: 1800 844 891 | E: orders@mhpower.com.au | W: mhpower.com.au

